

# **MOLYSLIDE®**

## **Lubricants**




**ANTI SEIZE COMPOUNDS**  
**SOLID LUBRICANTS**  
**PASTES**  
**LUBRICANTS**  
**RUST PROTECTION**  
**SEALANTS**  
**CLEANERS**



**MOLYSLIDE® Lubricants**

A-8141 Unterpremstätten - Bahnhofstr. 4 - Tel.+43 3136 55593 Fax. +43 3136 555 935 mail. [office@molslide.com](mailto:office@molslide.com)

[www.molslide.com](http://www.molslide.com)

|   | Product   | Description  | Units   |
|---|---|--|---|
|    | <b>MS 600</b><br><b>MOS/2 SOLID LUBRICANT PASTE</b><br>- 30°C up to + 450°C | Solid lubricant paste with an especially low friction coefficient for the assembling and running-in of sliding bearings, bushes, wheels, shafts ad sliding surfaces. Prevents fretting corrosion, stick-slip and tear and wear. Excellent dry running lubrication.   | Cans 1kg  |
|    | <b>MS 604</b><br><b>ANTI SEIZE COPPER</b><br>- 40°C up to + 1000°C          | Protects against seizure, corrosion, saltwater, clamping, high pressure, rust and for lubrication. For the lubrication of highly stressed bearings and sliding surfaces at low speed. Protection and easy dismantling. Lubricant paste for brake parts at cars and trucks.   | Cans 1kg<br>Cans 5kg<br>Barrel 180 kg<br>Spray 500 ml   |
|    | <b>MS 605</b><br><b>ANTI SEIZE CERAMIC</b><br>-40°C up to + 1400°C          | Against electrochemical corrosion, seizure, reaming, stick-slip and salt water. A metal free solid lubricant paste which is resistant to high temperatures. For easy dismantling of highly stressed parts in industry and on vehicles. Metal free lubricant paste for brake parts at cars and trucks.  | Cans 1kg<br>Cans 5kg<br>Barrel 180 kg<br>Spray 500 ml   |
|   | <b>MS 607</b><br><b>ANTI SEIZE GREY</b><br>- 180°C up to +1200°C            | Protects against oil carbon residues, seizure by corrosion, saltwater, reaming, rust and for lubrication. Protection and easy dismantling of screws, nuts and bolts, threads, turbines, brake parts, valve shafts, gaskets etc. Application in industry and on heavy vehicles. Lubricant paste for brake parts at cars and trucks.   | Cans 1kg<br>Cans 5kg<br>Barrel 180 kg<br>Spray 500 ml   |
|  | <b>MS 609</b><br><b>LONGTIME EP GREASE</b><br>- 30°C up to + 160°C          | Li-complex grease of extremely high quality. 3 – 5 times longer retention time in comparison with traditional greases. Completely water resistant, even against vapor and waste water. Ideal lubricant for construction machinery, machinery in industry, heavy vehicles, equipment in cement works at high temperatures and pressure.   | Cart. 400 g<br>Cans 5 kg<br>Cans 50 kg<br>Barrel 180 kg |
|  | <b>MS 610</b><br><b>MOLYSLIDE RB 2 MOS/2</b><br>- 20°C up to + 130°C        | Lithium soap grease with special additives. For the lubrication of normally and highly stressed rolling and sliding bearings under dusty and humid working conditions. For the improvement of the high pressure absorption and dry running properties this grease contains molybden-sulfide. Application at vehicles (wheel bearing grease), constructional machinery, commercial vehicles, in industry. | Cart. 400 g<br>Cans 5 kg<br>Cans 50 kg<br>Barrel 180 kg |
|  | <b>MS 612</b><br><b>MULTIPURPOSE GREASE EP</b>                              | A high quality universal grease for the lubrication of normally and highly stressed sliding and rolling bearings at vehicles of all kinds, constructional and agricultural machinery, machinery in industry and industrial plants according to DIN K2K-30. Excellent resistance to vibration and pressure.   | Cart. 400 g<br>Cans 5 kg<br>Cans 50 kg<br>Barrel 180 kg |
|  | <b>MS 625</b><br><b>CUTTING LUBRICANT</b>                                   | Cutting spray for economic and fast application when drilling, broaching, sawing, punching, milling and thread reaming, suitable for all metals, especially for high grade steels resistant to rust and acid. Reduces the friction resistance and increases the life time of tools. Especially recommended for the use on construction sites and for assembling works.                                   | Spray 500 ml  |
|  | <b>MS 626</b><br><b>CABLE &amp; GEAR LUBRICANT</b>                          | Special lubricant for the lubrication and care of cables, gear rims, bevel wheels and worm wheels, chains, toothed wheels, open gears etc. The lubricant is resistant to pressure and water and does not drip off. Penetrates immediately. Especially used in the building industries and industries in connection with the building industry.   | Spray 500 ml  |

|   | Product  | Description  | Units        |
|---|--|--|--------------|
|    | <b>MS 629</b><br><b>PTFE LUBRICANT WHITE</b>   | White PTFE lubricant for the lubrication of slow to medium running sliding and rolling bearings, guides, toothed wheels, wire ropes, sliding surfaces, roller chains and machinery elements. Also suitable for plastic parts. Excellent for rebound straps at doors and hinges at cars.        | Spray 500 ml |
|    | <b>MS 630</b><br><b>SUPER LUBE</b><br><b>PTFE OIL</b><br><b>- 40°C up to + 220°C</b>   | Multifunctional acid-free oil with PTFE solid lubricants. Use under extreme pressure and high temperatures. Also suitable for the lubrication and protection of plastic and elastomers. Transparent and without any smell. Cleans, lubricates, displaces water and loosens parts seized.       | Spray 500 ml |
|    | <b>MS 632</b><br><b>FOOD LUBRICANT</b>   | Special lubricant for the lubrication of bearings, guides, hinges etc. which get in touch with food.   | Spray 500 ml |
|   | <b>MS 633</b><br><b>UNIVERSAL EP</b><br><b>LUBRICANT-20°C up to + 120°C</b>            | Universal EP lubricant for the lubrication of slow and medium running sliding and rolling bearings, toothed wheels, wire ropes, sliding surfaces, roller chains and chains. It is very resistant to vibration and water and it has excellent properties against high pressure and penetration. | Spray 500 ml |
|  | <b>MS 634</b><br><b>CHAIN EP</b><br><b>LUBRICANT</b><br><b>- 20°C up to +120°C</b>     | High pressure grease for outer and inner lubrication of fast and slow running chains and wire ropes with high load. Penetrates quickly and has excellent adhesion properties. Decreases tear and wear and prevents corrosion. Suitable for O-rings.  | Spray 500 ml |
|  | <b>MS 635</b><br><b>SILICON OIL</b><br><b>LUBRICANT</b><br><b>- 40°C up to + 220°C</b> | 100% silicone oil used as sliding and separating agent. Ideal for the lubrication of all kinds of materials. Can be used as separating agent and for the care of rubber gaskets. Lubricates plastic parts, fine-mechanical parts etc. Completely transparent and without any smell.            | Spray 500 ml |

## Rust Protection / Protectors

|   |   |   |              |
|---|---|---|--------------|
|  | <b>MS 636</b><br><b>ZINC SPRAY</b><br><b>GREY</b>   | Cathodic rust protection with a good resistance against weathering and salt water according to DIN. Shock resistant and with good adhesion properties, can be welded and painted. Is drying fast, resistant to temperatures up to +360° C. Rust should be removed from parts to be protected. | Spray 500 ml |
|  | <b>MS 637</b><br><b>ZINC SPRAY</b><br><b>GLOSSY</b> | Cathodic rust protection with a good resistance against weathering and salt water according to DIN. Shock resistant and with good adhesion properties, can be welded and painted. Is drying fast, resistant to temperatures up to +360° C. Rust should be removed from parts to be protected. | Spray 500 ml |

|   | Product                            | Description  | Units        |
|---|------------------------------------|--|--------------|
|  | <b>MS 638</b><br><b>ALU SPRAY</b>  | Corrosion protection with excellent adhesion properties based on aluminium particles. For the protection of pipes, rims, kettles etc. Dries quickly and has excellent adhesion properties. Is also used for applications with optical improvement. Temperature resistant up to +350° C.                                | Spray 500 ml |
|  | <b>MS 639</b><br><b>NIRO SPRAY</b> | Corrosion protection with excellent adhesion properties based on V2A particles. For the protection of pipes, rims, kettles etc. Dries quickly and has excellent adhesion properties. Is also used for applications with optical improvement. Temperature resistant up to +350° C. Excellently resistant to salt water. | Spray 500 ml |

## Repair and Maintenance

|   |   |  |                            |
|---|---|--|----------------------------|
|    | <b>MS 642</b><br><b>WELD SEPARATING SPRAY</b>     | Separating spray without silicone , increases the lifetime of the welding nozzles, enables easier handling of the nozzles and prevents residues on work pieces. Do not spray on hot nozzles and work pieces – flammable.   | Spray 500 ml               |
|  | <b>MS 650</b><br><b>RUST SOLVENT WITH MOS / 2</b> | Special rust solvent with high penetration properties and an extremely strong solvent power. Due to the addition of disulphide better sliding properties are achieved. It displaces moisture, loosens rust and protects against corrosion.   | Spray 500 ml<br>Cans 20 lt |
|  | <b>MS 651</b><br><b>RUST SOLVENT FREEZE</b>       | Special product for loosening of freezed parts. Due to the ingredients the parts on which the spray is applied are shrinking. Special sliding agents ease the dismantling after evaporation of the cooling agent. Apply the product only on one of the parts to be dismantled. Do not spray onto the skin or into the eyes – risk of combustion. | Spray 500 ml               |
|  | <b>MS 652</b><br><b>CONTACT SPRAY</b>             | Oxyde dissolving contact spray, which removes disturbing corrosion layers and dirt from contacts. Special ingredients prevent further corrosion on plugs, connectors, tuners, resistors and therefore contact resistance and voltage loss are prevented.   | Spray 500 ml               |
|  | <b>MS 656</b><br><b>GASKET REMOVER</b>            | Loosens quickly and without any problems dried up, seized gaskets and gasket materials. Eases the removing of carbon residues on engine parts. Removes adhesives and colors. Not for use on plastic parts.   | Spray 500 ml               |

|   | Product   | Description  | Units                                    |
|---|---|--|--|
|  | <b>MS 685</b><br><b>MOTORSEAL</b><br><b>GASKET</b><br><b>- 70°C up to + 300°C</b> | For the production of all kinds of sealants in engine and machinery construction. Replaces all kinds of pre-cut gaskets and is resistant against most liquid media, like engine oils, cooling agents, mineral oils and many other liquids. Is excellently resistant against high temperatures. | Cart. 310 ml<br>Cart. 80 ml<br>Tube 85 g |

## Cleaner

|   |  |  |   |
|---|--|--|---|
|    | <b>MS 690</b><br><b>ASSEMBLY CLEANER</b>                 | Pollution free solvents in combination with special inhibitors for cleaning of all kinds of parts. Loosens oils, greases, resinified lubricants and residues. Can be applied before constructive bondings in industrial production.  | Spray 500 ml  |
|   | <b>MS 691</b><br><b>BRAKE CLEANER</b><br><b>SPRAY</b>    | Removes brake dust, resinified lubricants and residues of all kinds from brake parts, coupling parts, gear and engine parts. Pollution free solvents and ingredients, which protect from corrosion, loosen the residues quickly and vaporize. Also removes fresh PU-foam.  | Spray 600 ml<br>Cans 20 lt<br>Barrel 60 lt<br>Barrel 180 lt |
|  | <b>MS 692</b><br><b>UNIVERSAL FOAM</b><br><b>CLEANER</b> | Removes oil, grease, rust, wax, nicotinic residues, insect remainings, ink etc. Ideal as universal cleaner for glass, metal, plastic, varnished parts of cars, in household, hobby and garden as well as for busines and industry.   | Spray 600 ml  |
|  | <b>MS 693</b><br><b>ELECTRO CLEANER</b>                  | Combination of special solvents and citrus terpenes for careful cleaning. Loosens resinified lubricants, dust, grease and oil residues without damaging the isolation of windings.   | Spray 500 ml  |
|  | <b>PAINT MASTER</b><br><b>MARKING PAINT</b>              | Marking paint with illuminating power, resistant to weathering and moisture. Excellently resistant to UV light. It is equipped with two valves which allow the application on the ground as well as on vertical surfaces. Ideal for the building industry and trade in conneciton with the building industry, agriculture and forestry and industry. Colors: red, yellow, blue, green. | Spray 500 ml  |